Page 1/12



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Version number 01-00

Revision: 21.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Trade name: WoodColor m 6.15 W 100 +F 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Application of the substance / the mixture Coating agent Uses advised against This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet. 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Dörken Coatings GmbH & Co. KG Wetterstr. 58 58313 Herdecke Germany www.doerkencoatings.de Phone: +49 2330 63 243 Fax: +49 2330 63 100 243 Further information obtainable from: msds.coatings@doerken.de 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463 **SECTION 2: Hazards identification** 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS07 Skin Sens, 1 H317 May cause an allergic skin reaction. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. Hazard pictograms GHS07 Signal word Warning (Contd. on page 2) - DE/EN



according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Version number 01-00

Revision: 21.03.2024

Trade name: WoodColor m 6.15 W 100 +F

	(Contd. of page 1)
Hazard-	determining components of labelling:
2-octyl-2	H-isothiazol-3-one
1,2-benz	isothiazol-3(2H)-one
mixture o	of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
2-methyl	-2H-isothiazol-3-one
3-lodo-2	-propynylbutylcarbamate
Hazard	statements
H317 Ma	ay cause an allergic skin reaction.
H412 Ha	rmful to aquatic life with long lasting effects.
Precaut	ionary statements
P273	Avoid release to the environment.
P280	Wear protective gloves.
P302+P3	352 IF ON SKIN: Wash with plenty of soap and water.
P362+P3	364 Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Additior	nal information:
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or
	mist.
2.3 Othe	r hazards
Results	of PBT and vPvB assessment
PBT: No	t applicable.
	ot applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

CAS: 13463-67-7 EINECS: 236-675-5	Titanium dioxide Carc. 2, H351	10-25%
Reg.nr.: 01-2119489379-17-xxxx		
CAS: 112-34-5 EINECS: 203-961-6	2-(2-Butoxyethoxy)ethanol Eye Irrit. 2, H319	≥1-<10%
Reg.nr.: 01-2119475104-44-xxxx	Eye Init. 2, n319	
CAS: 55406-53-6 EINECS: 259-627-5	3-lodo-2-propynylbutylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.1-<0.25%
CAS: 2634-33-5 EINECS: 220-120-9 Reg.nr.: 01-2120761540-60-xxxx	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C≥ 0.05 %	≥0.025 - <0.05%

Page 3/12



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Version number 01-00

Revision: 21.03.2024

Trade name: WoodColor m 6.15 W 100 +F

CAS: 26520.20.4	0 cetyl 011 ieethierel 2 cre	(Contd. of page
CAS: 26530-20-1 EINECS: 247-761-7	2-octyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 ATE: LD ₅₀ oral: 125 mg/kg LD ₅₀ dermal: 311 mg/kg LC ₅₀ / 4 h inhalative: 0.27 mg/l Specific concentration limit: Skin Sens. 1A; H317: C≥ 0.0015 %	≥0.0025-<0.025%
CAS: 55965-84-9 Reg.nr.: 01-2120764691-48-xxxx	mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one	≥0.00025-<0.00159
CAS: 2682-20-4	Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 % 2-methyl-2H-isothiazol-3-one	<0.0015%
EINECS: 220-239-6 Reg.nr.: 01-2120764690-50-xxxx	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C \geq 0.0015 %	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Version number 01-00

Revision: 21.03.2024

(Contd. of page 3)

DÖRKEN[®]

Trade name: WoodColor m 6.15 W 100 +F

If skin irritation or rash occurs: Get medical advice/attention.

Take off immediately all contaminated clothing and wash it before reuse.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an opthalmologist.

After swallowing:

Rinse mouth thoroughly with water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage. Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Keep contaminated washing water and dispose of appropriately.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Version number 01-00

Revision: 21.03.2024

(Contd. of page 4)

DÖRKEN[®]

Trade name: WoodColor m 6.15 W 100 +F

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid prolonged, intensive skin contact and contact with the eyes.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 12

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with	limit values that require monitoring at the workplace:
112-34-5 2-(2-Bu	toxyethoxy)ethanol
AGW (Germany)	Long-term value: 67 mg/m³, 10 ppm 1.5(I);EU, DFG, Y, 11
IOELV (EU)	Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm
57-55-6 Propyle	ne glycol
MAK (Germany)	als Dampf und Aerosol;vgl.Abschn.IIb und Xc
55965-84-9 mixt	ure of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
MAK (Germany)	Long-term value: 0.2E mg/m³ vgl.Abschn.Xc
Regulatory infor	mation
AGW (Germany)	
IOELV (EU): (EU) 2019/1831
	(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Colour:

Odour:

Odour threshold:

Version number 01-00

Revision: 21.03.2024

DÖRKEN[®]

Trade name: WoodColor m 6.15 W 100 +F

(Contd. of page 5) Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area. Appropriate engineering controls Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air. Individual protection measures, such as personal protective equipment General protective and hygienic measures: Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Immediately remove all soiled and contaminated clothing Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. **Respiratory protection:** Breathing protection is always required when spraying. Use combination filter A2(-P2) according to EN 14387. Hand protection Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374. It is recommended to use long gloves to minimize contact by splashing. Material of gloves Nitrile rubber The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye/face protection Wear protective goggles to protect against splashing. Have eye wash bottle or eye rinse ready at work place. Professional Cooperative Rules - BGR 192 Use of eye and face protection Body protection: Impervious protective clothing **SECTION 9: Physical and chemical properties** 9.1 Information on basic physical and chemical properties **General Information Physical state** Fluid

Different according to colouring

Weak after glycol ethers

For mixtures not applicable.



according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Version number 01-00

Revision: 21.03.2024

Trade name: WoodColor m 6.15 W 100 +F

	(Contd. of p
Melting point/Freezing point:	Not security-related.
Boiling point or initial boiling point and boiling	g
range	100 °C (7732-18-5 water)
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Auto-ignition temperature:	Not applicable.
Decomposition temperature:	For mixtures not applicable.
pH at 20 °C	7.5-8.5
Viscosity:	Not security-related.
Solubility	Not security-related.
water:	Miscible / waterdilutable.
polar solvents:	Partly miscible.
non-polar solvents:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value	
Vapour pressure at 20 °C:	23 hPa (7732-18-5 water)
Density and/or relative density	
Density at 20 °C:	1.02-1.31 g/cm ³
Vapour density	Not applicable.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health	
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Softening point/range	
Oxidising properties	In its condition as supplied, the product is neither
Oxidising properties	flammable nor oxidising.
Evanaration rata	-
Evaporation rate	For mixtures not applicable.
Information with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
	VI III I



according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Version number 01-00

Revision: 21.03.2024

Trade name: WoodColor m 6.15 W 100 +F

		(Contd. of page 7)
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamn	nable	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

55406-53-6 3-lodo-2-propynylbutylcarbamate

Oral	LD_{50}	300-500 mg/kg (rat)
Dermal		>2,000 mg/kg (rat)
Inhalative	LC₅₀ / 4 h	0.5 mg/l (ATE)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met. **Carcinogenicity** Based on available data, the classification criteria are not met. **Reproductive toxicity** Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Version number 01-00

Revision: 21.03.2024

(Contd. of page 8)

List II; III

List II

Trade name: WoodColor m 6.15 W 100 +F

Aspiration hazard

The mixture contains no or only small amounts of materials which are classified as an aspiration hazard. It can therefore be assumed that the mixture is not an aspiration hazard. Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties). **11.2 Information on other hazards**

Endocrine disrupting properties

556-67-2 octamethylcyclotetrasiloxane

541-02-6 Decamethylcyclopentasiloxane

*

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

55406-53-6 3-lodo-2-propynylbutylcarbamate

EC₅₀ / 48 h	0.47 mg/l (daphnia) (OECD 202)		
EC₅₀ / 72 h	0.049 mg/l (Pseudokirchneriella subcapitata) (OECD 201)		
LC₅₀ / 96 h (dynamic)	0.145 mg/l (Oncorhynchus mykiss (rainbow trout))		
NOEC / 21 d	10 mg/l (daphnia) (OECD 211)		
NOEC / 28 d	0.014 mg/l (Pimephales promelas (fathead minnow)) (OECD 210)		

12.2 Persistence and degradability

55406-53-6 3-lodo-2-propynylbutylcarbamate

OECD 307 Aerobic And Anaerobic Transformation Soil 0.03-0.04 d (soil microorganisms) OECD 308 Simulation Biodegradation Agu Sed System 1-1.2 d (degradation half-life)

12.3 Bioaccumulative potential

55406-53-6 3-lodo-2-propynylbutylcarbamate

Partition Coefficient log Pow 2.8 (n-octanol/water) (OECD 117)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Version number 01-00

Revision: 21.03.2024

(Contd. of page 9)

Trade name: WoodColor m 6.15 W 100 +F

12.7 Other adverse effects

Behaviour in sewage processing plants:

55406-53-6 3-lodo-2-propynylbutylcarbamate

OECD 302B Zahn-Wellens Test	>70 % (activated sludge organisms)
OECD 303A Activated Sludge Units	100 % (activated sludge organisms)
EC ₂₀ / 3 h	8.2 mg/l (activated sludge organisms) (OECD 209)
ЕС ₅₀ / 3 h	8.2 mg/l (activated sludge organisms) (OECD 209)

Other information:

General notes: Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

HP14 Ecotoxic

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	j to IMO	
instruments	Not applicable.	

DE/EN





according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Version number 01-00

Revision: 21.03.2024

Trade name: WoodColor m 6.15 W 100 +F

UN "Model Regulation":

Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed. REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 55

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

Labelling according to Regulation (EC) No 2004/42

VOC limit 2010 for category e (WB): 130 g/l. This product contains max 130 g/l VOCs.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

(Contd. of page 10)

DÖRKEN®



according to 1907/2006/EC, Article 31

Printing date 21.03.2024

Version number 01-00

Revision: 21.03.2024

Trade name: WoodColor m 6.15 W 100 +F

		(Contd. of page 11)
	her information please consult the "Technical	
Misuse	may cause damage to health and environmer	nt.
Labelli	ng according to regulation (EC) No 528/201	12
Additio	onal information:	
Contain	ns protective agent for products in storage and	l coating protective agent.
Warnin	g! Hazardous respirable droplets may be form	ed when sprayed. Do not breathe spray or mist.
	nt phrases	
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H310	Fatal in contact with skin.	
H311	Toxic in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H330	Fatal if inhaled.	
H331	Toxic if inhaled.	
H351	Suspected of causing cancer.	
H372	Causes damage to organs through prolonge	ed or repeated exposure.
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effe	ects.
EUH07	1 Corrosive to the respiratory tract.	
	ication according to Regulation (EC) No 12	272/2008
	nsitisation	The classification of the mixture is generally based on
	ous to the aquatic environment - long-term	the calculation method using substance data
(chronic	c) aquatic hazard	according to Regulation (EC) No 1272/2008.
Date of	f previous version: 21.03.2024	l
Abbrev	viations and acronyms:	
	x. 4: Acute toxicity – Category 4	
	x. 2: Acute toxicity – Category 2	
	x. 3: Acute toxicity – Category 3 r. 1: Skin corrosion/irritation – Category 1	
	r. 1B: Skin corrosion/irritation – Category 1B	
	r. 1C: Skin corrosion/irritation – Category 1C	
	2: Skin corrosion/irritation – Category 2	
	n. 1: Serious eye damage/eye irritation – Category 1	
	2: Serious eye damage/eye irritation – Category 2 s. 1: Skin sensitisation – Category 1	
	s. 1A: Skin sensitisation – Category 1A	
	Carcinogenicity – Category 2	
	E 1: Specific target organ toxicity (repeated exposure) – C	
	Acute 1: Hazardous to the aquatic environment - acute aq	
•	Chronic 1: Hazardous to the aquatic environment - long-te Chronic 3: Hazardous to the aquatic environment - long-te	
	and more trazallous to the addatic environment - 1000-16	SIII aqualo hazalu – Calegoly J
	compared to the previous version altered.	