

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**Trade name: **LUCITE® 161 MetalProtect****1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Application of the substance / the mixture** Coating agent**Uses advised against**

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Dörken Coatings GmbH & Co. KG  
 Wetterstr. 58  
 58313 Herdecke  
 Germany  
 www.doerkencoatings.de

Phone: +49 2330 63 243

Fax: +49 2330 63 100 243

**Further information obtainable from:** msds.coatings@doerken.de**1.4 Emergency telephone number:**

Emergency CONTACT (24-Hour-Number):

GBK GmbH +49 (0)6132-84463

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2    H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3      H336 May cause drowsiness or dizziness.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

Trade name: **LUCITE® 161 MetalProtect**

(Contd. of page 1)

### Hazard pictograms



GHS02 GHS07 GHS09

**Signal word** Warning

#### Hazard-determining components of labelling:

n-Butyl acetate

Hydrocarbons, C9, aromatics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

1-Methoxy-2-propanol

#### Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P312 Call a doctor if you feel unwell.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains maleic anhydride. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

Vapours of the product are heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Vapours can form explosive mixtures with air.

In case of inhalation: Higher doses may lead to a narcotic effect.

#### Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

Trade name: **LUCITE® 161 MetalProtect**

(Contd. of page 2)

Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	≥10-≤25%
CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	Titanium dioxide Carc. 2, H351	10-25%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40-xxxx	Trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥10-<25%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Hydrocarbons, C9, aromatics Alternative CAS number: 64742-95-6 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335; STOT SE 3, H336, EUH066	≥2.5-≤10%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60-xxxx	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	<5%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36-xxxx	2-butoxyethanol Acute Tox. 3, H331; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD <sub>50</sub> oral: 1,200 mg/kg LC <sub>50</sub> / 4 h inhalative: 3 mg/l	<5%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	≥1-<5%
CAS: 7429-90-5 EINECS: 231-072-3 Reg.nr.: 01-2119529243-45-xxxx	aluminium powder (stabilised) Flam. Sol. 1, H228	≥1-<5%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-Methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	≥1-<5%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Asp. Tox. 1, H304, EUH066	≥1-<5%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32-xxxx	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<2.5%
CAS: 24468-28-8 EINECS: 246-279-4	1,3,5-Triazin-2,4,6-(1H,3H,5H)-trion, Zinksalz Aquatic Acute 1, H400; Aquatic Chronic 2, H411	≥0.25-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31-xxxx	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	<0.001%

(Contd. on page 4)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

**Trade name: LUCITE® 161 MetalProtect**

(Contd. of page 3)

**Additional information:**

All hydrocarbons used comply with note P (less than 0.1% benzene) of the CLP regulation.  
For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

**After inhalation:**

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

Wash with plenty of soap and water.

In case of skin reactions consult a physician. Do not scratch.

**After eye contact:**

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an ophthalmologist.

**After swallowing:**

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

**4.2 Most important symptoms and effects, both acute and delayed**

Allergic reactions

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Headache, dizziness, numbness, sickness/nausea, tiredness, stunning effect, dry skin, allergic reactions.

**4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:**

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**5.2 Special hazards arising from the substance or mixture**

Flammable liquid and vapour.

Can form explosive gas-air mixtures.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

(Contd. on page 5)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

**Trade name: LUCITE® 161 MetalProtect**

(Contd. of page 4)

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO) and nitrogen oxides (NO<sub>x</sub>). Inhalation may cause serious health damage. Under certain fire conditions, traces of other toxic gases cannot be excluded.

### 5.3 Advice for firefighters

#### Protective equipment:

Wear self-contained respiratory protective device.  
Wear fully protective suit.

#### Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources and ensure a well-ventilated room. Do not inhale fumes.  
Avoid contact with skin and eyes.

### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.

### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose of the material collected according to regulations.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Avoid the formation of ignitable and explosion- hazardous solution vapours.  
Ensure good ventilation/exhaustion at the workplace.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Material can become charged electrostatically. Anti-static clothing including shoes are recommended.  
Avoid contact with skin and eyes as well as inhalation of vapours.  
Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

#### Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.  
Use explosion-proof apparatus / fittings and spark-proof tools.  
Handle only outside or in explosion protected rooms.  
Fumes can combine with air to form an explosive mixture.

(Contd. on page 6)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

Trade name: **LUCITE® 161 MetalProtect**

(Contd. of page 5)

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

#### Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

#### Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

**Further information about storage conditions:** None.

**Storage class:** 3

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

##### 123-86-4 n-Butyl acetate

AGW (Germany)	Long-term value: 300 mg/m <sup>3</sup> , 62 ppm 2(I);AGS, Y
IOELV (EU)	Short-term value: 723 mg/m <sup>3</sup> , 150 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm

##### Hydrocarbons, C9, aromatics

IOELV (EU)	Long-term value: 100 mg/m <sup>3</sup> , 20 ppm (trimethylbenzole)
------------	---

##### 34590-94-8 Dipropylene glycol monomethyl ether

AGW (Germany)	Long-term value: 310 mg/m <sup>3</sup> , 50 ppm 1(I);DFG, EU, 11
IOELV (EU)	Long-term value: 308 mg/m <sup>3</sup> , 50 ppm Skin

##### 111-76-2 2-butoxyethanol

AGW (Germany)	Long-term value: 49 mg/m <sup>3</sup> , 10 ppm 2(I);EU, DFG; H, Y
IOELV (EU)	Short-term value: 246 mg/m <sup>3</sup> , 50 ppm Long-term value: 98 mg/m <sup>3</sup> , 20 ppm Skin

##### 107-98-2 1-Methoxy-2-propanol

AGW (Germany)	Long-term value: 370 mg/m <sup>3</sup> , 100 ppm 2(I);DFG, EU, Y
IOELV (EU)	Short-term value: 568 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm Skin

(Contd. on page 7)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

Trade name: **LUCITE® 161 MetalProtect**

(Contd. of page 6)

### 108-31-6 maleic anhydride

AGW (Germany)	Long-term value: 0.081 mg/m <sup>3</sup> , 0.02 ppm 1;=2.5=(I);DFG, Sah, Y, 11
---------------	---

#### Regulatory information

AGW (Germany): TRGS 900

IOELV (EU): (EU) 2019/1831

#### Ingredients with biological limit values:

### 111-76-2 2-butoxyethanol

BGW (Germany)	150 mg/g Kreatinin Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende, bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten Parameter: Butoxyessigsäure (nach Hydrolyse)
---------------	---

### 107-98-2 1-Methoxy-2-propanol

BGW (Germany)	15 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: 1-Methoxypropan-2-ol
---------------	---

**Regulatory information** BGW (Germany): TRGS 903

**Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls** Provide good ventilation and/or an exhaust system in the work area.

#### Appropriate engineering controls

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

#### Individual protection measures, such as personal protective equipment

##### General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

##### Respiratory protection:

Breathing protection is always required when spraying.

Use combination filter A2(-P2) according to EN 14387.

##### Hand protection

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374.

##### Material of gloves

Multi-layer glove - PE / EVAL / PE

(PE = polyethylene, EVAL = ethylene-vinyl alcohol copolymer)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 8)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

Trade name: **LUCITE® 161 MetalProtect**

(Contd. of page 7)

### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### Eye/face protection

Wear protective goggles to protect against splashing.

Have eye wash bottle or eye rinse ready at work place.

Professional Cooperative Rules - BGR 192 Use of eye and face protection

**Body protection:** Solvent resistant protective clothing

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

#### Physical state

Fluid

#### Colour:

Different according to colouring

#### Odour:

Strong after aromatic hydrocarbons

#### Odour threshold:

Not applicable for mixtures.

#### Melting point/Freezing point:

Not security-related.

#### Boiling point or initial boiling point and boiling range

120 °C (107-98-2 1-Methoxy-2-propanol)

#### Flammability

Flammable.

#### Lower and upper explosion limit

#### Lower:

0.6 Vol % (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

#### Upper:

14 Vol % (34590-94-8 Dipropylene glycol monomethyl ether)

#### Flash point:

39 °C

#### Auto-ignition temperature:

>200 °C (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

#### Decomposition temperature:

For mixtures not applicable.

#### pH

Mixture is non-soluble (in water).

#### Viscosity:

> 90 s (20°C / DIN 53211 / 4 mm)

> 60 s (20°C / ISO 2431 / 6 mm)

> 20,5 mm<sup>2</sup>/s (40°C)

#### Solubility

#### water:

Not miscible or difficult to mix.

#### polar solvents:

Not miscible or difficult to mix.

#### non-polar solvents:

Fully miscible.

#### Partition coefficient n-octanol/water (log value)

For mixtures not applicable.

#### Vapour pressure at 20 °C:

13 hPa (107-98-2 1-Methoxy-2-propanol)

#### Density and/or relative density

#### Density at 20 °C:

1.37-1.46 g/cm<sup>3</sup>

#### Vapour density

Not applicable.

(Contd. on page 9)



## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

Trade name: **LUCITE® 161 MetalProtect**

(Contd. of page 8)

### 9.2 Other information

#### Appearance:

Form: Fluid

#### Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

#### Change in condition

#### Softening point/range

Oxidising properties: The product is flammable, although not oxidising.

Evaporation rate: For mixtures not applicable.

### Information with regard to physical hazard

#### classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

## SECTION 10: Stability and reactivity

**10.1 Reactivity** Vapours can form explosive mixtures with air.

**10.2 Chemical stability** Product is stable under normal storage conditions.

**10.3 Possibility of hazardous reactions** No dangerous reactions known.

**10.4 Conditions to avoid** Keep away from heat sources, sparks and open flames.

**10.5 Incompatible materials:** strong oxidizing agents

(Contd. on page 10)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

Trade name: **LUCITE® 161 MetalProtect**

(Contd. of page 9)

### 10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** Based on available data, the classification criteria are not met.

#### LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

#### 111-76-2 2-butoxyethanol

Oral	LD <sub>50</sub>	1,200 mg/kg (ATE)
Inhalative	LC <sub>50</sub> / 4 h	3 mg/l (ATE)

#### Specific symptoms in biological assay:

##### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

##### Serious eye damage/irritation

Splashes of solvent may cause irritation to the eye and reversible damage.

Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** May cause drowsiness or dizziness.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

##### Aspiration hazard

Due to the viscosity (see section 9), classification as an aspiration hazard is omitted.

Based on available data, the classification criteria are not met.

##### General notes:

Inhalation of solvent concentrations in excess of the OEL or MAK limit values can lead to health damage such as irritation of the mucous membranes and respiratory tract, damage to the kidneys and liver, and impairment of the central nervous system. Symptoms: headaches, dizziness, fatigue, muscle weakness, narcotic effect and, in exceptional cases, loss of consciousness. Prolonged or repeated contact with the product impairs the skin's natural lipid replenishment and causes the skin to dry out. The product can enter the body through the skin. Splashes of solvent may cause irritation to the eye and reversible damage.

##### Additional toxicological information:

##### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

(Contd. on page 11)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

Trade name: **LUCITE® 161 MetalProtect**

(Contd. of page 10)

### 11.2 Information on other hazards

#### Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

Toxic to aquatic life with long lasting effects.

#### 123-86-4 n-Butyl acetate

EC <sub>50</sub> / 48 h	44 mg/l (Daphnia magna (big water flea))
EC <sub>50</sub> / 72 h	647.7 mg/l (Pseudokirchneriella subcapitata)
LC <sub>50</sub> / 96 h	18 mg/l (Pimephales promelas (fathead minnow))

#### 7779-90-0 Trizinc bis(orthophosphate)

EC <sub>50</sub> / 48 h	0.33-0.66 mg/l (Daphnia magna (big water flea)) (OECD 202)
EC <sub>50</sub> / 72 h	0.14 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC <sub>50</sub> / 96 h	0.17 mg/l (Oncorhynchus mykiss (rainbow trout))

#### Hydrocarbons, C9, aromatics

EC <sub>50</sub> / 48 h	3.2 mg/l (Daphnia magna (big water flea))
LC <sub>50</sub> / 96 h	9.2 mg/l (Oncorhynchus mykiss (rainbow trout))

#### 111-76-2 2-butoxyethanol

EC <sub>50</sub> / 24 h	1,800 mg/l (Daphnia magna (big water flea))
EC <sub>50</sub> / 72 h	911 mg/l (Selenastrum capricornutum)
LC <sub>50</sub> / 96 h	1,700 mg/l (Oncorhynchus mykiss (rainbow trout)) >100 mg/l (Lepomis macrochirus (bluegill))

#### 1314-13-2 zinc oxide

EC <sub>50</sub> / 48 h	0.17 mg/l (daphnia)
LC <sub>50</sub> / 96 h	0.14 mg/l (Oncorhynchus mykiss (rainbow trout))
IC <sub>50</sub> / 72 h	0.17 mg/l (algae) literature

### 12.2 Persistence and degradability

#### 123-86-4 n-Butyl acetate

OECD 301D Closed-Bottle Test	83 % (28d) (O <sub>2</sub> consumption) readily biodegradable
------------------------------	--

#### Hydrocarbons, C9, aromatics

OECD 301F Manometric Respirometry Test	78 % /O <sub>2</sub> consump (28d) readily biodegradable
--	---

(Contd. on page 12)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

Trade name: **LUCITE® 161 MetalProtect**

(Contd. of page 11)

<b>111-76-2 2-butoxyethanol</b>	
OECD 301B CO <sub>2</sub> -Evolution Test (Sturm Test)	90.4 % (28d) readily biodegradable
<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</b>	
Biodegradation	80 % (28d) readily biodegradable
<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</b>	
OECD 301F Manometric Respirometry Test	80 % (28d) readily biodegradable

### 12.3 Bioaccumulative potential

<b>123-86-4 n-Butyl acetate</b>	
OECD 117 Log Kow (HPLC method)	2.3 (n-octanol/water) (25 °C; pH 7)
<b>111-76-2 2-butoxyethanol</b>	
Partition Coefficient log Pow	0.81 (n-octanol/water) (25 °C; pH 7)
<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</b>	
Partition Coefficient log Pow	5-6.7 (n-octanol/water)

**12.4 Mobility in soil** No further relevant information available.

### 12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

**PBT:** Not applicable.

**vPvB:** Not applicable.

### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

### 12.7 Other adverse effects

**Other information:**

#### General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

#### European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable

(Contd. on page 13)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

Trade name: **LUCITE® 161 MetalProtect**

(Contd. of page 12)

HP14 | Ecotoxic

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR, IMDG, IATA

UN1263

#### 14.2 UN proper shipping name

ADR

1263 PAINT, ENVIRONMENTALLY HAZARDOUS

IMDG

PAINT, MARINE POLLUTANT

IATA

PAINT

#### 14.3 Transport hazard class(es)

ADR



Class

3 (F1) Flammable liquids.

Label

3

IMDG



Class

3 Flammable liquids.

Label

3

IATA



Class

3 Flammable liquids.

Label

3

#### 14.4 Packing group

ADR, IMDG, IATA

III

#### 14.5 Environmental hazards:

Product contains environmentally hazardous substances: Hydrocarbons, C9, aromatics

Marine pollutant:

Symbol (fish and tree)

Special marking (ADR):

Symbol (fish and tree)

#### 14.6 Special precautions for user

Warning: Flammable liquids.

Hazard identification number (Kemler code):

30

EMS Number:

F-E,S-E

(Contd. on page 14)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

Trade name: **LUCITE® 161 MetalProtect**

(Contd. of page 13)

<b>Stowage Category</b>	A
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
<b>Transport/Additional information:</b>	
<b>ADR</b>	
<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>Transport category</b>	3
<b>Tunnel restriction code</b>	D/E
<b>IMDG</b>	
<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

##### Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 28

#### **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

#### **REGULATION (EU) 2019/1148**

#### **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

#### **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

(Contd. on page 15)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

**Trade name: LUCITE® 161 MetalProtect**

(Contd. of page 14)

### Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

### Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

#### National regulations:

#### Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

**Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

#### Labelling according to Regulation (EC) No 2004/42

VOC limit according to 2004/42/EC for category i (SB) and maximum VOC content: see lid.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".  
Misuse may cause damage to health and environment.

#### Labelling according to regulation (EC) No 528/2012

#### Additional information:

Contains maleic anhydride. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### Wording of H and EUH phrases (number and full text)

- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

(Contd. on page 16)

**Safety data sheet**

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025

Version number 07-00 (replaces version 06-03)

Revision: 11.02.2025

**Trade name: LUCITE® 161 MetalProtect**

(Contd. of page 15)

H351 Suspected of causing cancer.  
 H372 Causes damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.  
 EUH071 Corrosive to the respiratory tract.

**Classification according to Regulation (EC) No 1272/2008**

Flammable liquids	On basis of test data
Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**Date of previous version:** 23.01.2024**Version number of previous version:** 06-03**Abbreviations and acronyms:**

ATE: Acute toxicity estimate values  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Flam. Sol. 1: Flammable solids – Category 1  
 Acute Tox. 4: Acute toxicity – Category 4  
 Acute Tox. 3: Acute toxicity – Category 3  
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Resp. Sens. 1: Respiratory sensitisation – Category 1  
 Skin Sens. 1A: Skin sensitisation – Category 1A  
 Carc. 2: Carcinogenicity – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

**\* Data compared to the previous version altered.**